



TANK™ S/SZ SERIES

FOUR-WHEEL STEER COMMERCIAL ZERO-TURN RIDERS

DESIGNED FOR PROFESSIONAL DAILY USE ON CHALLENGING TERRAIN. IDEAL FOR PROPERTIES UP TO 20 ACRES.

FEATURES

POWER STEERING

54" OR 60" FABRICATED
COMMERCIAL-GRADE DECK

COMMERCIAL-GRADE
KOHLER® COMMAND® PRO,
KAWASAKI® FX, AND
KOHLER COMMAND PRO
EFI SERIES ENGINES

INDUSTRY'S STRONGEST
HEAVY-DUTY RAIL FRAME

QUICK-ADJUST
STEERING COLUMN

PIVOTING FRONT AXLE

LIMITED 3-YEAR
COMMERCIAL WARRANTY*
WITH NO HOUR LIMITATION

*See specifications for warranty information.

INDUSTRY-LEADING ZERO-TURN STRENGTH AND PRECISION.

Meet the commercial zero turn rider that raises the bar for zero-turn performance—and the expectations of professional landscapers everywhere. Experience an unmatched combination of professional-grade strength, comfort, stability and maneuverability.

INDUSTRY-LEADING FEATURES. THAT'S THE STRENGTH OF THE **CUB CADET ADVANTAGE.**




INCREDIBLE MANEUVERABILITY AND CONFIDENCE

Productivity and efficiency begin with control. And the TANK S/SZ series delivers with patented Synchro Steer™ technology pioneered by Cub Cadet. The stability of four-wheel steering and ease of steering wheel control combine for the highest level of precision, efficiency and confidence on nearly any terrain.

MORE POWERFUL POWER MANAGEMENT

It's the powertrain designed to increase productivity and maximize profits. The muscular Kohler Command PRO EFI engine produces top results and more fuel efficiency than carbureted models while its e-governor maximizes power to the deck for ideal cutting performance in all weather and terrain conditions. And, the Smart Start Clutch provides smooth PTO engagement maximizing belt life.



UNBEATABLE CORROSION PROTECTION AND DURABILITY

The exclusive Cub Triple Guard Corrosion Defense System™ with e-Coat delivers automotive-grade corrosion resistance against wear and tear and the elements, ensuring complete protection of critical components for years of reliable performance and a lasting professional appearance.



Cub Cadet

YOUR INDEPENDENT DEALER—EXPERT SERVICE. LOCALLY OWNED.

THE ADVICE, SELECTION AND SUPPORT YOU NEED TO FIND THE RIGHT FIT IS AT YOUR LOCAL CUB CADET DEALER.

ATTACHMENTS

THAT BOOST PRODUCTIVITY ALL YEAR ROUND

Whether you're working through the heat of summer or the dead of winter, our attachments are made to boost your earning potential the whole year through. So you can maximize your profits while getting the best results possible.




POWER LIFT



TRIPLE BAGGER/DUMP HOPPER WITH POWER ASSIST



12-VOLT OUTLET KIT



LIGHT KIT



ULTRA TRACTION TIRE/RIM



72" SNOW BLADE

ALSO AVAILABLE:

- MULCH KIT
- CASTER WHEEL KIT

This brochure is for advertisement purposes only. The product depictions are not meant to be used or relied upon as a substitute for the safety and use information that is published in the respective operator's manual. Before operating the machine, read, understand and follow all instructions in the manual and on the machine.

Specifications and programs are subject to change without notice. Images may not reflect dealer inventory and/or unit specifications.

* As rated by Kohler, all power levels are rated at 3600 RPM per SAE J1940 gross.

** As rated by Kawasaki, horsepower tested in accordance with SAE J1995 and rated in accordance with SAE J2723 and certified by SAE International

† See your local Cub Cadet Independent Dealer for warranty details. Cub Cadet commercial products are intended for professional use. 773-05725 Printed in U.S.A. 12/14 © 2015 Cub Cadet



ENGINE	TANK S 60	TANK SZ 54	TANK SZ 60	TANK SZ 60 EFI
Engine Type	Commercial-grade Kohler® Command PRO® V-Twin OHV	Commercial-grade Kawasaki® FX Series V-Twin OHV	Commercial-grade Kawasaki FX Series V-Twin OHV	Commercial-grade Kohler Command PRO EFI V-Twin OHV
Engine Displacement/ Orientation	747cc/Vertical	852cc/Vertical	852cc/Vertical	824cc/Vertical
Engine Horsepower	23.5 HP*	27 HP**	27 HP**	33 HP*
Engine Fuel	Gasoline			
Lubrication/Filter	Full pressure w/ spin-on filter			
Cooling System	Air			
Air Cleaner	Heavy-duty canister air filter			
Alternator	12V – 20 amp regulated	12V – 20 amp regulated	12V – 20 amp regulated	12V – 25 amp regulated
Fuel Capacity	7.5-gallon tank	Twin 7.5-gallon tanks (15-gal. total)	Twin 7.5-gallon tanks (15-gal. total)	Twin 7.5-gallon tanks (15-gal. total)
Fuel Gauge	Standard (mounted on tank)			
DRIVE SYSTEM				
Drive System	HTE PARKER™ Torqpack 10 cc pumps, 240cc wheel motors	HTG PARKER™ Torqpack 14cc pumps, 280cc wheel motors	HTG PARKER™ Torqpack 14cc pumps, 280cc wheel motors	HTG PARKER™ Torqpack 14cc pumps, 280cc wheel motors
Ground Speed	Fwd: 10.5 mph Rev: 6 mph	Fwd: 12 mph Rev: 6 mph	Fwd: 12 mph Rev: 6 mph	Fwd: 12 mph Rev: 6 mph
Hydraulic Fluid	Castrol Edge w/ Syntec Power 5W-50 7 qt. total capacity			
Hydraulic Oil Filter	Individual filter cartridges standard			
Return to Neutral	Standard			
Braking/Parking Brake	Dynamic drum, hand lever control			
STEERING				
Caster Wheel Pivot Bearings	Tapered roller, greasable			
Front Axle	Pivoting, steerable front wheel w/ cast-iron			
Controls	Steering wheel control w/ comfort grip, quick-adjust steering column			
CHASSIS				
Frame	Heavy-duty rail frame 3/8" x 5" laser cut steel w/ tie-down slots			
TIRES				
Front Tire Size	15" x 6.5" – 8" (turf)			
Rear Tire Size	24" x 9.5" x 12" (turf) (smart traction tread/self clean)	24" x 12" – 12" (turf) (wide track, smart traction tread/self clean)	24" x 12" – 12" (turf) (wide track, smart traction tread/self clean)	24" x 12" – 12" (turf) (wide track, smart traction tread/self clean)
DIMENSIONS				
Length/Width/Height	86.5" / 49.5" / 73.5"	86.5" / 49.5" / 73.5"	86.5" / 61.5" / 74"	86.5" / 61.5" / 74"
Wheelbase	54"			
Front Track Width	43"			
Rear Track Width	50"	53"	53"	53"
Weight (approx.)	1,250 lbs.	1,250 lbs.	1,300 lbs.	1,300 lbs.
MOWER DECK				
Deck Size/Type	60" sloped-nose triple blade (high lift)	54" sloped-nose triple blade (high lift)	60" sloped-nose triple blade (high lift)	60" sloped-nose triple blade (high lift)
Deck Style/System	Floating			
Deck Blades	Triple-blade/High-lift blade (standard)			
Deck Construction	10-gauge fabricated with 7- and 10-gauge reinforcements			
Deck Drive	Belt – Kevlar® B-section			
Deck Lift	Single pedal, spring-assisted			
Deck Height Adjust.	1" – 5" (in .25" increments)			
Blade Spindle	Cast-aluminum construction			
Deck PTO	Electronic fingertip engagement			
Front Anti-Scalping Wheels/Nose Roller	2 standard, greasable/2-nose wheels			
Rear Anti-Scalping Rollers/Striper	Full width, adjustable w/ stability rod			
ADDITIONAL SPECIFICATIONS				
ROPS	Standard, foldable/2-position lock (ISO 21299, OSHA 1928)			
Monitor/Hour Meter	Standard			
Seat Type	High-back, premium suspension with lumbar adjust angled back and Elasticity Vibration Control (EVC) comfort control seat w/ armrests			
Cup Holder	Standard			
Storage Box	—	Standard	Standard	Standard
Rear Bumper & Hitch	Rear bumper w/ hitch standard	Heavy-duty rear bumper w/ hitch standard	Heavy-duty rear bumper w/ hitch standard	Heavy-duty rear bumper w/ hitch standard
WARRANTY†				
	2-yr limited commercial warranty† (no hour limitation) or 4-yr/800 hour limited residential warranty†	3-year limited commercial warranty (no hour limitation)	3-year limited commercial warranty (no hour limitation)	3-year limited commercial warranty (no hour limitation)